



Versatile Portable Projector with High Brightness

FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 3600 lumens of brightness and 20,000:1 contrast ratio for clear, crisp and bright presentations
- WXGA (1280 x 800) native resolution and support up to maximum WUXGA (1920x1200) resolution
- Compact and lightweight at 2.6kg for easy portability
- A long lamp life up to 10,000 hours for low Total Cost of Ownership (TCO)
- Audio ready with built-in 2 watt audio speaker, audio-in and audio-out ports



From meeting room to presentations anywhere on the road

The Vivitek DW284-ST delivers exceptional digital images with a high degree of vibrancy thanks to 3600 lumens of brightness and a contrast ratio of 20,000:1. Featuring native WXGA resolution the DW284-ST is designed for a wide variety of applications. Their compact size at just 2.6 kg allows for easy transportation between different meeting rooms or classrooms.



DW284-ST SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	3600 ANSI Lumens
	Native Resolution	WXGA (1280 x 800)
	Max. Supported Resolution	WUXGA (1920 x1200) @60Hz
	Contrast Ratio	20:000:1
	Native Aspect Ratio	16:10
	Keystone Correction	Vertical: +/-40°
Optical	Throw Ratio	0.49 :1
	Image Size (Diagonal)	50" - 100"
	Projection Distance	0.53m - 1.09m
	Projection Lens	F=2.65, f=7.2mm
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x2), HDMI Number of Ports (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RS-232, USB miniB (Service)
General	Lamp Life and Type	5,500 / 7,000 / 10,000 Hours (Normal / Eco. / Dynamic Eco. Mode), 210W
	Speakers	2 W
	Dimensions (W x D x H)	331 x 244 x 105mm
	Weight	2.6 kg
	Noise Level	32dB / 29dB (Normal / Eco. Mode)
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 210W (Eco. Mode), 250W (Normal Mode), <0.5W (Standby)
	Warranty	Entry Warranty: 2 years projector / 1 year on lamp or 1.000 hours whichever comes first, Education Warranty: 5 years projector / 3 years on lamp or 2.000 hours whichever comes first
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (XX5810005600), Remote Control P/N (XX5040005400), Carrying Case P/N (XX3520000800)