



INCEILING ELECTRIC SCREEN (IES)

When you need to hide a screen in the ceiling this is your natural choice. The screen will be integrated in the suspended ceiling in your home or at the office.

CASSETTE/COLOUR

The screen cassette is made of aluminium and is powder coated in white.

REMOTE CONTROL (KP300A)

See separate product information for Kingpin Remote Control System KP300A.

MOTOR

The motor is a tubular motor that is placed inside the axle tube. The running time is max 5 min, after that the overheating protection may be activated.

POWER

The power cord for the screen is 5 meters long with the control box mounted in the middle of the cord. The control box works as the receiver of the remote control. All Kingpin electric screens are CE-certified and operated by 100-230V / 50-60Hz. The fuse in the control box is 6,3 A.

SCREEN FABRIC/GAIN

For a natural picture, the screen fabric is matte white with a gain of 1,0. The screen fabric is made of PVC coated fibreglass.

FORMAT 1:1

The screen fabric has 1:1-format, it has a white frontside (no black borders). The screen has a black reverse side for better contrast, depth and to prevent backlight.

END POSITIONS

The end positions of the screen can be adjusted very easily and with high precision. The adjustment screws are placed on the motor on the right hand side of the cassette.

MOUNTING

The screens can be mounted in the ceiling with the enclosed mounts. The included screw bars are 1 meter long but can be cut to the desired length.

TECHNICAL SPECIFICATION: INCEILING ELECTRIC SCREEN

Article number	Size (inch)	Format	Gain matte white	Fabric size (mm)	Borders (mm)	Black drop (mm)	Viewing area (mm)	Length cassette (mm)	Hight cassette (mm)	Width cassette (mm)	Weight net (kg)	Packaging L x W x H (mm)
IES210-1:1	117"	1:1	1,0	2100x2650	0	0	2100x2400	2230	116	165	22/24	2420x200x150
IES240-1:1	134"	1:1	1,0	2400x2650	0	0	2400x2400	2530	116	165	24/26	2720x200x150